

LIEBIG® self-undercutting anchor SUPERPLUS ILS



Cross references

Cleaning brush
 Blow-out pump
 Tool belt
 Hammer drill SDS-plus
 Installation tool for through bolts
 Cordless hammer drill
 Torque wrench

Application range

- > Machinery
- > Base plates
- > Small edge and centre distances



Base materials

- Also suitable for
- > Natural stone
 - > Non-cracked concrete

Properties

- > Galvanized zinc-plated steel
- > With M8 internal thread
- > Automatic self-undercutting, unique heavy-duty anchor for push through installation
- > The easiest, quickest and simplest solution on the market.
- > Cost-effective: No special drills, undercutting or setting tools required
- > Minimal expansion forces allow for small centre and edge distances
- > For dry indoor use

Technical data



Characteristic values						Permitted loads non-cracked concrete C20/25		Permitted loads cracked concrete C20/25		
	Type	d_i [mm]	Thread [mm]	d_0 [mm]	h_{ef} [mm]	T_{inst} [Nm]	N_{Rec} [kN]	V_{Rec} [kN]	N_{Rec} [kN]	V_{Rec} [kN]
	M8-14/80	10	M8	14	80	25	13.9	8.6	7.6	8.6

Order description	Nominal size [mm]	L [mm]	d_0 [mm]	h_1 [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
LIEBIG SUPERPLUS ILS M8-14/80	M8	95	14	100	25		9 650 814 080	4061245001128