

DABO® screw TKR-4-4.8



Application range

- > To secure roofing membrane and insulating material to sheet steel substructures $\geq 1.5 \text{ mm} \leq 4.0 \text{ mm}$
- > For combination with stress plates
- > For new buildings


Properties

- > Case-hardened steel
- > Climadur-coated – high-quality coating to improve corrosion protection (15 Kesternich cycles, DIN 50018, 1997)
- > Can be delivered belted for installation tool EOCSET or pre-assembled and belted with stress plate HTK-2G for installation tool ECOSET HTK.
- > With bugle head

Applications



Technical specifications



Certifications



Length determination (minimum lengths)

Sheet steel	Total panel thickness + 20 mm
Timber	Total panel thickness + 30 mm

Cross references

Stress plate HTV 82/40 TK
 Stress plate HTV 82/40 F
 Stress plate HTV 40 RU
 Stress plate HTK-2G 50
 Stress plate EcoTek 50
 Stress plate HTK-S
 Flat roof profile FP
 Bit cross recess



EJOT® installation tool ECOSET available as rental equipment
 Article number G000000076



EJOT® installation tool ECOSET available as rental equipment.
 Article number G000000072

Product online



Order description	Length [mm]	Thread length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
TKR-4-4.8x70	70	56	500		3438070639	4061245012438
TKR-4-4.8x90	90	56	500		3438090639	4061245012421
TKR-4-4.8 x110	110	56	250		3438110639	4061245012414

Compatibility acc. to ETA-07/0013

	HTV 82/40	HTE 82/40	HTV 82/40 TK	HTV 82/40 F	HTV 40 RU	HTK 2G 50xL	HTK 2G 75xL	EcoTek 50	EcoTek-T 50	HTK-S	Flat roof profile FP
TKR-4-4.8			X	X	X	X	X	X	X	X	X