

## DEKTITE® EZi-Seal Set



### Application range

- > For waterproofing pipes on corrugated metal or fibre cement roofs

### Properties

- > Version EDPM (black)
- > Temperature resistance EPDM (black)  
permanent 50 °C to +115 °C, short-term up to +150 °C

### Included in delivery

- 1 pipe flashing
- 1 self-drilling screw set - optionally folding blind rivet set

### Cross references

Hose clamp  
Tightener  
Joint sealant

### Benefits

- > Non-absorbent, closed-cell sealing surface
- > Seals under compression even on wet surfaces
- > Seals without use of a joint sealant through existing seal strip.
- > No interference of thermal elongation of pipes
- > No fatigue fractures
- > 20-year warranty on material

### Note

Use folding blind rivets for fibre cement boards. Profile height max. 45 mm.




1. Adjust DEKTITE® to the pipe.



2. Adjust DEKTITE® to the profiled sheet and mark.



3. Adjust DEKTITE® to the shape of the profiled sheet.



4. Fasten DEKTITE® with self-drilling screws or folding blind rivets.

### Product online



Order description	For pipe diameter [mm]	Base [mm]	Roof pitch [°]	Content screws [pieces]	PU [set]	Price/1 [EUR]	Article number	EAN
DFE 100 EZ	0–35	100 x 100	0–60	8	1		8200004706	4061245013947
DFE 101 EZ	5–55	139 x 139	0–35	8	1		8200104706	4061245013794
DFE 103 EZ	5–127	221 x 221	0–35	16	1		8200304706	4061245013770
DFE 104 EZ	75–175	280 x 280	0–35	20	1		8200404706	4061245013756
DFE 106 EZ	125–230	363 x 363	0–35	28	1		8200604706	4061245013732
DFE 107 EZ	150–300	456 x 456	0–35	32	1		8200704706	4061245013718
DFE 109 EZ	230–508	681 x 681	0–35	40	1		8200904706	4061245013695

Order information: Other dimensions upon request